



Art.-Nr: YFLSO-LANS-1001
LED floodlight "SOLID"
wall / ceiling surface mounting,



[More information](#)



TECHNICAL DATA


Dimensions	
Product dimensions Length	175 mm
Product dimensions Width	165 mm
Product dimensions Height	34 mm
Product weight	700 g
Color	
Color	Black
Housing material	
Housing material	Aluminum die-cast
Certification	
Certification	CE, RoHS
Insulation class	1
Protection type (IP)	IP66
Shock resistance level (IK)	8
Electrical connection	
Rated power	10 W
Input voltage AC	220-240V / 50-60Hz V
Power factor	0.9 PF




power supply	
DC suitability	Yes
Electrical design	with internal control gear
Light data	
Light source	LED
Rated luminous flux	1400 lm
Colour rendering index	> 70 Ra
Beam angle	97 °
Color temperature	4000 K
Light color	740
Service life	120000 h, L80
Light yield	140 lm/w
Temperatures	
Ambient temperature (Min)	-30 °C
Ambient temperature (Max)	50 °C
CASAMBI Products	
Input voltage DC	216 V
Mounting	
Mounting	Recessed mounting, Wall mounting



TEXT.LICHTVERTEILUNG





YFLSO-LANS-1001