



SOLUTIONS IN SAFETY + LIGHTING

www.rp-group.com

Art.-Nr: EARL428SC-AZ Emergency light Self-contained Surface mounting, 8 h, , IP40, Zinc die-cast, Anthracite,

High-grade zinc-aluminium safety luminaire for fitting on the ceiling. The round safety luminaire, which adapts to the ceiling design.

Thanks to the snap-in mechanism between the upper and lower part, the luminaire has a harmonious look and appears closed all the way round. The luminaire is connected to the mains in the ceiling section. When closed, the luminaire is powered via contact plugs. This greatly simplifies mounting and makes convenient connection possible despite the small size of the luminaire.

Automatic monitoring of safety luminaire with SelfControl. The innovative integrated lens holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and corridor lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options.



More information

www.rp-group.com/en/item/EARL428SC-AZ




Technical Data

Luminaire type	Emergency light
Mounting	Surface mounting
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast
Housing color	Anthracite
Protection type (IP)	IP40

Impact resistance (IK)	≥ 3
Certification	WEEE, CE, 5 years warranty
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	8 h
Battery	LiFePO4 3,2V/3,3Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230V
Input frequency	50 / 60 Hz
Power max.	3W
Power maintained	1,9W
Power non-maintained	0,2W
Ambient temperature maintained mode	-5°C to 40°C
Ambient temperature non-maintained mode	-5°C to 30°C
Height	39mm
Diameter	104mm
Weight	0.37
Weight incl. packaging	0.41
Connection cross-section	2.5mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	130lm
Luminous flux emergency	125lm
Customs tariff number	94056180
GTIN	4260682158703


Technical drawing



Accessory List

- ILD-APA-02 - IL surface-mounted adapter
- LFPN3233.01 - LiFePO4 Battery

Related Products

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Sim lum mo
EARL423SC		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itse
EARL423SC- AZ		SelfControl (SC)	Single battery	RAL 7016	€	no	high	no	unlimited	itse
EARL423WL		Wireless Professional (WL)	Single battery	RAL 9003	€€	yes	low	yes	1,000 per system	cen
EARL423WL- AZ		Wireless Professional (WL)	Single battery	RAL 7016	€€	yes	low	yes	1,000 per system	cen
EARL428SC		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itse
EARL428WL		Wireless Professional (WL)	Single battery	RAL 9003	€€	yes	low	yes	1,000 per system	cen
EARL428WL- AZ		Wireless Professional (WL)	Single battery	RAL 7016	€€	yes	low	yes	1,000 per system	cen

As of: 12.06.2026 - Subject to technical changes and errors.