



SOLUTIONS IN SAFETY + LIGHTING

www.rp-group.com

Art.-Nr: EAQL428WB-AZ Emergency light Self-contained Surface mounting, 8 h, , IP40, Zinc die-cast, Anthracite,

High-grade zinc-aluminium safety luminaire for fitting on the ceiling. The square safety luminaire, which adapts to the ceiling design.

Thanks to the snap-in mechanism between the upper and lower part, the luminaire has a harmonious look and appears closed all the way round. The luminaire is connected to the mains in the ceiling section. When closed, the luminaire is powered via contact plugs. This greatly simplifies mounting and makes convenient connection possible despite the small size of the luminaire.

Wireless control and monitoring for small installations of up to 50 luminaires with [Wireless Basic](#). The [innovative integrated lens](#) holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and corridor lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options.



More information

www.rp-group.com/en/item/EAQL428WB-AZ




Technical Data

Luminaire type	Emergency light
Mounting	Surface mounting
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast

Housing color	Anthracite
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	WEEE, CE, 5 years warranty
Insulation class	2
Supply	Self-contained
Monitoring	Wireless Basic (WB)
Bridging time	8 h
Battery	LiFePO4 3,2V/3,3Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230V
Input frequency	50 / 60 Hz
Power max.	3,4W
Power maintained	2,3W
Power non-maintained	0,4W
Ambient temperature maintained mode	-5°C to 40°C
Ambient temperature non-maintained mode	-5°C to 40°C
Depth	104mm
Width	104mm
Height	39mm
Weight	0.39
Weight incl. packaging	0.43
Connection cross-section	2.5mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	130lm
Luminous flux emergency	125lm
Customs tariff number	94056180
GTIN	4260682158826

Technical drawing



Accessory List

ILD-APA-02 - IL surface-mounted adapter

LFPN3233.01 - LiFePO4 Battery

As of: 12.06.2026 - Subject to technical changes and errors.