



SOLUTIONS IN SAFETY + LIGHTING

www.rp-group.com

Art.-Nr: EAQL029ML

Emergency light Centralised power supply systems

Surface mounting, CPS, , IP40, Zinc die-cast, White,

LED safety luminaire for surface mounting on the ceiling and illuminating escape and emergency routes in accordance with DIN EN 60598-1, DIN EN 60598-222 and DIN EN 1838.

The discreet zinc aluminium ceiling luminaire inconspicuously adapts to the ceiling. The use of diffuser lenses and powerful LED ERT technology achieves optimum light distribution and escape and emergency route illumination. The innovative integrated lens holder with a rapid fitting fixture permits the flexible use of various lens types depending on the specific application.

A round lens and hall lens are supplied with every luminaire.

Control and monitoring via [central power supply system](#). The [innovative integrated lens](#) holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and corridor lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options.



More information

www.rp-group.com/en/item/EAQL029ML



Technical Data

Luminaire type

Mounting

Pictograph


Emergency light

Surface mounting

No

Illuminant	LED
Housing material	Zinc die-cast
Housing color	White
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	WEEE, CE, TÜV Rheinland Type approved, ENEC
Insulation class	2
Supply	Centralised power supply systems
Monitoring	Central power supply (ML)
Bridging time	CPS
Battery	/
Operating mode	single luminaire switching
Input voltage AC	230V
Input frequency	50 / 60 Hz
Input voltage DC	216V
Power max.	4,6W
Power maintained	4,6W
Power non-maintained	1,2W
Ambient temperature maintained mode	-20°C to 30°C
Ambient temperature non-maintained mode	-20°C to 40°C
Depth	104mm
Width	104mm
Height	39mm
Weight	0.31
Weight incl. packaging	0.35
Connection cross-section	2.5mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	Yes
Luminous flux mains	360lm
Luminous flux emergency	360lm
Customs tariff number	94056180
GTIN	4260766552731




Technical drawing



Accessory List

ILD-APA-02 - IL surface-mounted adapter

Related Products

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	System
EAQL029ML-AZ		Central power supply (ML)	Central power supply	RAL 7016	€€€	Yes	low	Yes	1,920 per system	System
EAQL529CC		CoreCompact 24 (CC)	Central power supply	RAL 9003	€€	Yes	low	Yes		System
EAQL529CC-AZ		CoreCompact 24 (CC)	Central power supply	RAL 7016	€€	Yes	low	Yes		System

As of: 12.06.2026 - Subject to technical changes and errors.