



SOLUTIONS IN SAFETY + LIGHTING

www.rp-group.com

Art.-Nr: EERL433SC-AZ

Emergency light Self-contained

Ceiling mounting, 3 h, , IP20, Zinc die-cast, Anthracite,

High-grade zinc-aluminium safety luminaire for fitting in the ceiling.

The compact design permits mounting in a 68mm opening in the ceiling. Alongside the usual recessed ceiling mounting, it can also be mounted in conventional and fire protection sockets. It is secured with ease using tension springs or a screw connection on the box.

Automatic monitoring of safety luminaire with **SelfControl**. The **innovative integrated lens** holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and corridor lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options.



More information

[www.rp-group.com/en/item/
EERL433SC-AZ](http://www.rp-group.com/en/item/EERL433SC-AZ)




Technical Data


Luminaire type	Emergency light
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast

Housing color	Anthracite
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE, 5 years warranty
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	LiFePO4 3,2V/1,2Ah
Operating mode	Non-maintained / maintained
Input voltage AC	180V - 230V
Input frequency	50 Hz
Power max.	4,2W
Power maintained	3,3W
Power non-maintained	0,9W
Ambient temperature maintained mode	-5°C to 40°C
Ambient temperature non-maintained mode	-5°C to 40°C
Height	4mm
Diameter	88mm
Installation dimensions Diameter	68mm
Weight	0.32
Weight incl. packaging	0.45
Connection cross-section	2,5mm²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	255lm
Luminous flux emergency	255lm
Customs tariff number	94056180
GTIN	4260766556036


Technical drawing



Lochausschnitt EER / EEQ



EEx023: 74mm
EEx029: 68mm



EEx029: Schalterdose notwendig (nicht im Lieferumfang enthalten)



Accessory List

LFPN3212-SET-2AKKU - LiFePO4 Battery

As of: 23.06.2026 - Subject to technical changes and errors.