



SOLUTIONS IN SAFETY + LIGHTING

www.rp-group.com

Art.-Nr: QBW421SC-BM

General light, Emergency light Self-contained Universal, 1 h, , IP44, Polycarbonate, White,

Round plastic LED general-purpose luminaire, as combined safety luminaire in a timeless design.

Alongside the general-purpose lighting, it also includes an integrated safety light function. When mounting, the emergency light LED can be swung out without the need for tools, to perfectly illuminate the escape and emergency routes when mounted on a wall, for example.

Automatic monitoring of safety luminaire with **SelfControl**. The integrated motion detector **(BM)** reliably detects movements and automatically turns on the light in mains operation.



More information

[www.rp-group.com/en/item/
QBW421SC-BM](http://www.rp-group.com/en/item/QBW421SC-BM)




Technical Data

Luminaire type	General light, Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP44
Impact resistance (IK)	6

Certification	WEEE, CE, 5 years warranty
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	1 h
Battery	LiFePO4 3,2V/1,2Ah
Operating mode	Non-maintained / maintained
Input voltage AC	180V - 250V
Input frequency	50 Hz
Power max.	18,5W
Power maintained	17,7W
Power non-maintained	1,4W
Ambient temperature maintained mode	-5°C to 40°C
Ambient temperature non-maintained mode	-5°C to 40°C
Height	98mm
Diameter	339mm
Weight	1.51
Weight incl. packaging	1.73
Connection cross-section	2,5mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	1800lm
Luminous flux emergency	470lm
EOF	0.26
Customs tariff number	94056180
GTIN	4262483020920

Technical drawing

QBW



Accessory List

LFPN3212-SET-2AKKU - LiFePO4 Battery
As of: 23.06.2026 - Subject to technical changes and errors.