



Art.-Nr: ROPA4201ML
General light, Safety luminaire Central power supply
Ceiling mounting, ML, Central power supply, , IP20, Metal,
Housing color



The Highpower LED panel for suspended ceilings offers you the highest brightness of approx. 4,500 lm at the best price. That's about 135 lm per watt!

The cover is made of PMMA plastic and therefore UV resistant which prevents yellowing.

The Highpower LED Panel cleverly combines energy-saving general lighting with the prescribed emergency lighting.

- LED 33W
- IP20
- For 620mm grid ceilings



More information



TECHNICAL DATA

Luminaire type	General light, Safety luminaire
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Housing material	Metal
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE
Insulation class	2
Supply	Central power supply
Monitoring	ML
Bridging time	Central power supply
Operating mode	Standby circuit / permanent circuit
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	216 V
Power max.	38 W
Power DS	38 W



Power BS	1,5 W
Depth	620 mm
Width	620 mm
Height	10 mm
Weight	3.67
Weight incl. packaging	3.75
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	3600 lm
Luminous flux emergency	3600 lm
Customs tariff number	94054210
Country of origin	CHINA
EAN	4260581710439

RELATED PRODUCTS

Art-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
ROPA4201										
ROPA4201SC		SelfControl	Single battery		€	no	high	no	unlimited	itself

As of: 28.06.2024 - Subject to technical changes and errors.