



**Art.-Nr: ROPA4201SC**  
**General light, Safety luminaire Single Battery**  
**Ceiling mounting, SelfControl, 3 h, , IP20, Metal, Housing color**

The Highpower LED panel for suspended ceilings offers you the highest brightness of approx. 4,500 lm at the best price. That's about 135 lm per watt!

The cover is made of PMMA plastic and therefore UV resistant which prevents yellowing.

The Highpower LED Panel cleverly combines energy-saving general lighting with the prescribed emergency lighting.

- LED 33W
- IP20
- For 620mm grid ceilings



[More information](#)



## TECHNICAL DATA

Luminaire type	General light, Safety luminaire
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Housing material	Metal
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE
Insulation class	2
Supply	Single Battery
Monitoring	SelfControl
Bridging time	3 h
Operating mode	Standby circuit / permanent circuit
Input voltage AC	230 V
Input frequency	50 Hz
Input voltage DC	- V
Power max.	36 W
Power DS	33 W



Power BS	2 W
Depth	620 mm
Width	620 mm
Height	10 mm
Weight	3.7
Weight incl. packaging	3.78
Connection cross-section	1.5 mm <sup>2</sup>
Switching input	Yes
Emergency light blocking	No
Battery connection	Clip
Dimming function	No
Luminous flux mains	3600 lm
Luminous flux emergency	660 lm
Customs tariff number	94054210
Country of origin	CHINA
EAN	4260349828307

## RELATED PRODUCTS

Art-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
ROPA4201										
ROPA4201ML		ML	Central power supply		€€€	Yes	low	Yes	1,920 per system	central

As of: 29.06.2024 - Subject to technical changes and errors.