



Art.-Nr: ROPA4202SC
General light, Safety luminaire Single Battery
Ceiling mounting, SelfControl, 3 h, , IP20, Metal, Housing color

The Highpower LED panel for suspended ceilings offers you the highest brightness of approx. 4,500 lm at the best price. That's about 135 lm per watt!

The cover is made of PMMA plastic and therefore UV resistant which prevents yellowing.

The Highpower LED Panel cleverly combines energy-saving general lighting with the prescribed emergency lighting.

- LED 33W
- IP20
- For 620mm grid ceilings



[More information](#)



TECHNICAL DATA

| | |
|------------------------|-------------------------------------|
| Luminaire type | General light, Safety luminaire |
| Mounting | Ceiling mounting |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Metal |
| Protection type (IP) | IP20 |
| Impact resistance (IK) | ≥ 3 |
| Certification | Waste disposal, CE |
| Insulation class | 2 |
| Supply | Single Battery |
| Monitoring | SelfControl |
| Bridging time | 3 h |
| Operating mode | Standby circuit / permanent circuit |
| Input voltage AC | 230 V |
| Input frequency | 50 Hz |
| Input voltage DC | - V |
| Power max. | 36 W |
| Power DS | 33 W |



| | |
|--------------------------|---------------------|
| Power BS | 2 W |
| Depth | 620 mm |
| Width | 620 mm |
| Height | 10 mm |
| Weight | 3.7 |
| Weight incl. packaging | 3.78 |
| Connection cross-section | 1.5 mm ² |
| Switching input | Yes |
| Emergency light blocking | No |
| Battery connection | Clip |
| Dimming function | No |
| Luminous flux mains | 3600 lm |
| Luminous flux emergency | 660 lm |
| Customs tariff number | 94056120 |
| Country of origin | CHINA |

RELATED PRODUCTS

| | | | | | | | | | | |
|----------|-------|------------|--------|-------|------------|---------------|-------------------|--------------------|-----------------|-----------------------------|
| Art.-No. | Image | Monitoring | Supply | Color | Investment | Automatic log | Maintenance level | Remote maintenance | max. luminaires | Single luminaire monitoring |
|----------|-------|------------|--------|-------|------------|---------------|-------------------|--------------------|-----------------|-----------------------------|

As of: 29.06.2024 - Subject to technical changes and errors.