




Art.-Nr: WAF529CC-AZ
Safety luminaire Centralised power supply systems
Wall mounting, CoreCompact 24 (CC), CPS, , IP20, Zinc die-cast, Anthracite



High-grade zinc die-cast safety luminaire for surface mounting on the wall.

The radiating characteristics run parallel to the wall to help perfectly illuminate escape and emergency routes.

Control and monitoring via central 24 V low-power system.



More information

www.rp-group.com/en/item/WAF529CC-AZ



TECHNICAL DATA


Luminaire type	Safety luminaire
Mounting	Wall mounting
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast
Housing color	Anthracite
Protection type (IP)	IP20
Impact resistance (IK)	4
Certification	WEEE, CE
Insulation class	3
Supply	Centralised power supply systems
Monitoring	CoreCompact 24 (CC)
Bridging time	CPS
Battery	/
Operating mode	Standby circuit / permanent circuit
Input voltageAC	24 V
Power max.	4,1 W
Power DS	4,1 W
Power BS	0,4 W
Ambient temperature DS	-5 °C - 40 °C
Ambient temperature BS	-5 °C - 40 °C



Depth	53 mm
Width	193 mm
Height	115 mm
Weight incl. packaging	0.03
Connection cross-section	2.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Luminous flux mains	420 lm
Luminous flux emergency	420 lm
Customs tariff number	94056180
EAN	4260682157560



TECHNICAL DRAWING



As of: 11.10.2024 - Subject to technical changes and errors.